

Board Type	Board Position	G Area Pad Location	Value	Tolerance %
DP1	14	7/8	47Ω	5
		15/16, 17/18, 19/20, 21/22, 23/24, 25/26	56Ω	5
DP2	15	23/24	22K	5
		23/33	100μF	5
DP3	16	15/16, 19/20	2.2K	5
		23/31	330pF	5
		1/9	0.01μF	20
DP6	5	1/7, 13/19	10μF	5
		2/10	0.33μF	5
		11/12, 31/32, 33/34	56Ω	5
		21/28	22μF	5
		14/18	2.2K	5
		20/24, 24/28	DIODE	
DP7	6	2/10	0.033μF	5
		11/19	0.68μF	5
		12/20	0.01μF	5
		21/27	1000pF	5
		29/30	2.2K	5
DP9	10	1/2, 3/4, 5/6, 7/8, 9/10, 11/12, 13/14, 15/16	DIODE	
DP10	11	2/8	0.033μF	5
		10/16	6.8μF	5
		17/18	10K	5
		19/25, 20/26	1.0μF	5
		27/28	DIODE	
DP11	12	2/10	0.047μF	5
		3/13, 13/23, 14/24, 25/33	100μF	5
		26/34	68μF	5
		27/33	10μF	5
		6B1/6B11, 6B3/6B12, 6B5/6B13	56Ω	5
28/32	2.2K	5		

Board Type	Board Position	Area Reference															
		1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	7A	7B		
DP 1	14	11	18	11	06	11	18	12	06	12		12					
DP 2	15	06	15	06	02	06	02	06	26	06	26	06		15			
DP 3	16	06	12	06	06	06		01	01	08	14		03	06	14		
DP 6	5	16	129	02	03	26	02	02	27	06	129						
DP 7	6	01	129	01	13	02	129	01	08	06		06		05	26		
DP 8	7	06	06	06	15	06		06		06	33	06	33	06	33		
DP 9	10	06	06	06	01	08	01	06	01	06	15	06		06			
DP10	11	17	129	03	129	03	129	15	129	01	09	01	08				
DP11	12	16	06	08	27	26	27	01	129	06	129	01		26			

NOTE

- 1 On all boards decoupling capacitors C1, C2 & C3 are 10μF ± 20%. Catalogue NY 9137
- 2 D.C. Supplies to all boards
 - + 6V pins 2, 31, 34, 63
 - 6V pins 3, 35
 - 0V pins 1, 32, 33, 64